

Mobile Sand Filling Systems

SANDfloh[®]

Type 200E

Dimensions (l x w x h):
approx. 1900 x 750 x 1300 mm
Turning radius: 1250 mm
Sand content: approx. 200 l



Type 200 with hand-guided lift-truck

Dimensions (l x w x h):
approx. 1750 x 750 x 1180 mm
Sand content: approx. 200 l



Technical Data and Specific Features:

- independent of external air and electric power supplies during the sand filling process at the rail vehicles
- compact design, low weight
- ease of operation
- Sandfloh 100: manoeuvrable either manually or by means of a forklifter
- Sandfloh 200: manoeuvrable by means of a special hand-guided lift-truck with a gradability of up to 20 %
- Sandfloh 200E: with integrated electric drive
- filled from sand storage silos, big-bag equipments or sand bags
- sand filling hose including filling nozzle (registered design)
- sand filling capacity approx. 10 l/min
- internal air and electric power supply sufficient to fill approx. 1000 - 1200 l brake sand
- integrated dust extraction
- protected control elements for electric and pneumatic functions
- colour RAL 1028 yellow

SANDfloh®



Type 100

Dimensions (l x w x h):
approx. 950 x 750 x 1170 mm
Sand content: approx. 100 l

KLEIN
Anlagenbau AG

KLEIN Anlagenbau AG
Konrad-Adenauer-Str. 200
D-57572 Niederfischbach
Phone ++49 (0) 27 34 / 5 01-3 01
Telefax ++49 (0) 27 34 / 5 01-3 27
e-mail: info@klein-ag.de
<http://www.klein-ag.de>

